



STARCRAFT


SoftFlex™ HTV




Maroon
SCSF-MAROON




Crimson
SCSF-CRMSN



Red
SCSF-RED




Bright Red
SCSF-BRTRED




Orange
SCSF-ORN




Pastel Orange
SCSF-PSTLORNG




Tennessee Orange
SCSF-TNORNG




Old Gold
SCSF-OLDGLD



Yellow
SCSF-YLW



Bright Yellow
SCSF-BRTYLW




Sulu Green
SCSF-SULUGRN



Key Lime
SCSF-KEYLIME



Light Green
SCSF-LTGRN




Green
SCSF-GRN




Olive Drab Green
SCSF-ODGRN




Dark Green
SCSF-DKGRN




Mint
SCSF-MINT




Tiffany Blue
SCSF-TIFFBLU



Dusty Blue
SCSF-DSTYBLU



Light Blue
SCSF-LTBLU




Sky Blue
SCSF-SKYBLU




Royal Blue
SCSF-RYLBLU




Navy Blue
SCSF-NVYBLU




Purple
SCSF-PRPL




Plum
SCSF-Plum




Lavender
SCSF-LVNDR




Lilac
SCSF-LLC




Pink
SCSF-PNK




Bubble Gum
SCSF-BBLGUM




Coral
SCSF-CORAL



Blush
SCSF-BLSH




Ivory
SCSF-IVRY




Buttercream
SCSF-BTTRCRM



Linen White
SCSF-LNNWHT




White
SCSF-WHT




Metallic Silver
SCSF-MTCSLVR




Grey
SCSF-GRY



Charcoal
SCSF-CHRCL




Black
SCSF-BLK




Brown
SCSF-BRN




Chocolate
SCSF-CHCLT



Metallic Copper
SCSF-MTCCPPR



Metallic Gold
SCSF-MTCGLD




Fluorescent Yellow
SCSF-FLUYLW



Fluorescent Pink
SCSF-FLUPNK



Fluorescent Orange
SCSF-FLUORG



Fluorescent Green
SCSF-FLGRN

**Features:**

Applies to: Cotton, Polyester,
Cotton/Polyester Blends, Tri-Blends*
Layerable: Yes
Thickness 90 micron
Finish: Matte/Flat
Stretchable: Yes
Carrier: Tacky for easier weeding
REACH/CPSIA Compliance: Yes**

Application Instructions:

Temperature: 285°F
Time: 8-10 Seconds
Pressure: Medium to Firm
Peel: Warm

Care/Wash Instructions:

Wait 24 Hours Before Wash
No harsh detergents or bleach
Tumble Dry Low Heat***

Notes:

* Application to blends that contain high levels of Rayon/Viscose or Spandex/Elastan should be applied with caution. Application at 265°F with two presses of 4-5 seconds each with garment allowed to cool between presses is recommended.

** REACH stands for Registration, Evaluation, Authorization and Restriction of Chemicals. REACH is a regulation of the European Union, adopted to improve the protection of human health and the environment from the risks that can be posed by chemicals, while enhancing the competitiveness of the EU chemicals industry. It also promotes alternative methods for the hazard assessment of substances in order to reduce the number of tests on animals. CPSIA is the Consumer Product Safety Improvement Act which is designed to allow the U.S. Consumer Products Safety Commission (CPSC) to better regulate the safety of products made and imported for sale in the U.S. CPSIA also contains regulations that are intended to make products for children under age 12 safer by requiring manufacturers and importers to show that these products do not have harmful levels of lead and phthalates.

*** Hang to dry is recommended to increase longevity of the garment and heat transfer vinyl. Drying with heat may also shrink the garment and cause puckering of the heat transfer vinyl so caution is advised.